

EUROLUB HLP ISO-VG 32

Description

HLP is blended with high-quality base oils and modern additives, carefully formulated to ensure optimal performance.
Effective zinc-based components provide long-lasting protection against ageing.
The product can be purified during processing using ultra-fine filtration without losing any of its active ingredients.

Can be used with

DIN 51 524 / Teil 2
FZG-Test A8, 3/90
Schadenskraftstufe: >12

ISO 11158
AIST 126 + 127
ASTM D6158
SAE MS 1004
JCMAS P041 HK
GM LS 2

Delivery

Art.-No. 504020	20 Liter	can
Art.-No. 504060	60 Liter	drum
Art.-No. 504208	208 Liter	drum
Art.-No. 504100	Container	800 – 3.000 litre
Art.-No. 504000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.876
Viscosity at 40°C	mm ² /s	DIN 51 562	32.7
Viscosity at 100°C	mm ² /s	DIN 51 562	5.4
Viscosityindex (VI)	-	DIN ISO 2909	98
Flash point (COC)	°C	DIN ISO 2592	220
Pourpoint	°C	DIN ISO 3016	-30