

EUROLUB HVLP ISO-VG 68

Description

HVLP is blended with high-quality base oils and modern additives, carefully formulated to ensure optimal performance. Effective zinc-based components provide long-lasting protection against ageing. The product can be purified during the manufacturing process using ultra-fine filtration without losing any of its active ingredients.

Can be used with

DIN 51 524 / Teil 3
FZG-Test A8, 3/90
Schadenskraftstufe: >12

ISO 11158
SIS SS 155434
ASTM D-6158
SAE MS 1004
JCMAS P041 HK
GM LS 2
AIST 127+136
Denison Filterability TP 02100

Delivery

Art.-No. 516020	20 Liter	can
Art.-No. 516060	60 Liter	drum
Art.-No. 516208	208 Liter	drum
Art.-No. 516100	Container	800 – 3.000 litre
Art.-No. 516000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.878
Viscosity at 40°C	mm ² /s	DIN 51 562	67.5
Viscosity at 100°C	mm ² /s	DIN 51 562	10.8
Viscosityindex (VI)	-	DIN ISO 2909	151
Flash point (COC)	°C	DIN ISO 2592	232
Pourpoint	°C	DIN ISO 3016	-39