

EUROLUB BIO-KETTENÖL UWS

Description

BIO-KETTENÖL UWS is a rapidly biodegradable chainsaw oil. It is produced from vegetable oils and toxicologically safe additives, which do not harm the environment as they are broken down by microorganisms within a short time. BIO-KETTENÖL UWS has excellent viscosity-temperature characteristics, particularly good cold resistance and, thanks to its adhesive and lubricating properties, offers high protection against wear and corrosion whilst being economical to use.

Shelf life: At least 18 months at a storage temperature of -15 °C to +25 °C.

The specifications may vary within the permissible tolerances due to raw material and manufacturing factors.

CEC-L33-T-82 = 97%

Delivery

Art.-No. 539005	4 x 5 Liter	can
Art.-No. 539020	20 Liter	can
Art.-No. 539060	60 Liter	drum
Art.-No. 539208	208 Liter	drum
Art.-No. 539100	Container	800 – 3.000 litre
Art.-No. 539000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.915
Viscosity at 40°C	mm ² /s	DIN 51 562	90.1
Flash point (COC)	°C	DIN ISO 2592	250
Pourpoint	°C	DIN ISO 3016	-30