

EUROLUB DRAHTSEILFLUID

Description

DRAHTSEILFLUID is a wire rope preservative, compliant with DSB 80. A relubricant for the lubrication and preservation of wire ropes. Thanks to its excellent adhesion and penetrating properties, it has also proven effective as an underbody and cavity protection for motor vehicles.

DRAHTSEILFLUID is used for the care and maintenance of a wide variety of wire ropes. Areas of application include, for example, ropes used in industrial settings, as well as ropes in large-scale open-cast mining machinery or excavators.

DRAHTSEILFLUID is available as a spray or in liquid form and can be applied to cleaned rope surfaces at normal temperature by spraying, brushing, rolling or similar methods. Once the aromatic-free solvent has evaporated – which takes 2–8 hours depending on climatic conditions – the lubricating film is fully formed. The optimum application temperature is 20°C.

DRAWSTRING FLUID contains solvents, which ensure excellent creeping properties. Based on a solid mass, a fully formed lubricating film remains.

Store in the original, unopened container at a maximum of +30°C. If stored below +10°C, warm to 30°C and homogenise before use.

Delivery

Art.-No. 718600	12 x 600 ml	Spray
Art.-No. 718001	12 x 1 Liter	bottle

Technische Daten

Data	Value
Chemical composition	High-viscosity components derived from petroleum processing, containing inhibitors and dissolved in a solvent.
Density	0.89 g/ml
Flash point	Approx. 30°C (DIN EN ISO 2719)
Notes	Stir before use; shake spray cans well!