

EUROLUB KÜHLERSCHUTZ READY-MIX UNIVERSAL RTU

Description

COOLANT PROTECT D-30 is a nitrite-, amine-, phosphate-, borate- and silicate-free coolant based on ethylene glycol, which must be diluted with water before use.

COOLANT PROTECTION D-30 contains high-quality corrosion inhibitors and provides optimum corrosion protection for all metals and metal alloys used in the cooling system, including aluminium (it can be used in cooling systems with all-aluminium engines, including as a lifetime fill).

COOLANT D-30 is an OAT and is miscible with most ethylene glycol-based coolants. For optimum corrosion protection and to prevent sludge formation, use in undiluted form is recommended.

- Protection against corrosion, cavitation and deposits.
- Foam reduction.
- Suitable for all antifreeze agents; however, use in conjunction with galvanised pipes or tanks is not recommended !!!

Can be used with

AFNOR 15-601
ASTM D3306
SAE J1034
BMW N600.69.0
BS 6580
Citroen (PSA B74 5110)
CUNA NC956-16
Ford WSS-M97B44-D
GM B 040 0240
Honda Type 2
Isuzu
Jaguar/Land Rover: STJLR.651.5003
MB 326.0/-2/-3/-5/-6 (*)
Nissan
Opel 6277M (B 040 1065)
Peugeot (PSA B71 5110)
Renault RX Type D
Saab (6901 599)
Toyota
Volvo
VW TL 774 C/D/F/G/J
(VW G11/G12/G12+/G12++/G13)
Audi, Seat, Skoda

Product Information



Delivery

Art.-No. 832001	12 x 1 Liter	bottle
Art.-No. 832004	4 x 4 Liter	can
Art.-No. 832020	20 Liter	can
Art.-No. 832060	60 Liter	drum
Art.-No. 832208	208 Liter	drum