

# 95 16 200

## Cable Shears with twin cutting edge



**PATENTED**



- for cutting copper and aluminium cables
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- easy cutting with one-hand operation
- initial and final cut (upper and lower blade) allows cables of up to 20 mm dia. to be cut
- low handforce required due to favourable lever ratio and special blade geometry
- guard prevents operators' fingers being pinched
- adjustable bolted joint, self-retaining screw
- High-grade special tool steel, forged, oil-hardened

<b>Article No.</b>	95 16 200
<b>EAN</b>	4003773026761
<b>Tool</b>	chrome plated
<b>Handles</b>	insulated with multi-component grips, VDE-tested
<b>Insulation standard</b>	IEC 60900 DIN EN 60900
<b>Cutting capacity copper cable, multiple-stranded (diameter) Ø mm</b>	20
<b>Cutting capacity copper cable, multiple-stranded mm<sup>2</sup></b>	70
<b>Nominal size</b>	200 mm
<b>AWG</b>	2/0
<b>Length mm</b>	200
<b>Net weight g</b>	340



Initial cut: using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.



Final cut: after cutting the sheath in the front profile the conductors in the rear part are cut. Initial cut in the front profile, final cut in the rear profile - to keep it as easy as possible.

technical change and errors excepted

