

95 16 200 SB

Cable Shears with twin cutting edge



PATENTED



- for cutting copper and aluminium cables
- not suitable for steel wire and hard drawn copper conductors
- precision ground, hardened blades
- clean and smooth cut without crushing and deformation
- easy cutting with one-hand operation
- initial and final cut (upper and lower blade) allows cables of up to 20 mm dia. to be cut
- low handforce required due to favourable lever ratio and special blade geometry
- guard prevents operators' fingers being pinched
- adjustable bolted joint, self-retaining screw
- High-grade special tool steel, forged, oil-hardened

Article No.	95 16 200 SB
EAN	4003773040910
Tool	chrome plated
Handles	insulated with multi-component grips, VDE-tested
Insulation standard	IEC 60900 DIN EN 60900
Cutting capacity copper cable, multiple-stranded (diameter) Ø mm	20
Cutting capacity copper cable, multiple-stranded mm²	70
AWG	2/0
Length mm	200
Net weight g	362



Initial cut: using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.



Final cut: after cutting the sheath in the front profile the conductors in the rear part are cut. Initial cut in the front profile, final cut in the rear profile - to keep it as easy as possible.

technical change and errors excepted

