



intAct Bike-Power GEL

Sealed maintenance-free GEL battery | electrolyte thickened into a gel-like mass | wet charged

Art.No.

GEL12-4A-BS

Japancode

YTR4A-BS

Volt	12V
Capacity	2,5 AH (c20)
CCR -18°C (EN)	60 A (EN)
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 kg/l (25°)
Size (LxWxH)	113 x 48 x 85 mm
Weight	1,1 kg
Pos. of Terminal	4
Terminal	S-6.3
Base plate	-









Usage




For heavy loads, including ABS

Delivers 30% more starting power for modern motorcycles with many electrical consumers and covers consumption peaks. Low self-discharge, bike starts reliably even after up to 3 months. Our recommendation if many consumers are installed or the motorcycle is rarely used.


- **» Even more cycle-resistant** than Bike-Power AGM and Bike-Power SLA of the same box size.
- » Low self-discharge. For seasonal use.
- Very high vibration-resistance. Electrolyte thickened into a gel-like mass.
- » 30% more starting power than a conventional battery of the same box size. For motorcycles with many consumers, including ABS.
- » Sealed maintenance-free battery. Refilling is neither possible nor necessary.
- » Wet charged. Ready to use.

Size

Kasten: GEL12-4A-BS



Terminal S-6.3



Base plate -

As of 26.08.2024

